## NSN 5930-01-027-5379

Sensitive Switch - Page 1 of 2



View Online at https://aerobas

View Online at https://aerobasegroup.com/nsn/5930-01-027-5379
Body Style:
Bushing/hole mounted
Overall Length:
Between 0.250 inches and 0.320 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.500 inches
Overall Height:
0.859 inches
Overall Width:
0.250 inches
Body Length:
Between 0.250 inches and 0.320 inches
Body Width:
0.250 inches
Body Height:
0.438 inches
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Style:
Round
Actuator Diameter:
0.125 inches
Actuator Height:
0.093 inches
Actuator Free Position Height:
0.437 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
2.0 ounces
Switch Actuating Force:

**Actuator Movement:** 

5.0 ounces

Between 0.050 pretravel inches and 0.012 overtravel inches and 0.012 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:** 

3.000 amperes resistive dc and 10.000 amperes resistive ac

## NSN 5930-01-027-5379

Sensitive Switch - Page 2 of 2



i ei ii ii iai Tybe And Quantity.	Tε	rminal	Type	And	Quantity:	
-----------------------------------	----	--------	------	-----	-----------	--

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0