

View Online at <https://aerobasegroup.com/nsn/5930-01-027-5379>

Body Style:

Bushing/hole mounted

Overall Length:

Between 0.250 inches and 0.320 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Overall Height:

0.859 inches

Overall Width:

0.250 inches

Body Length:

Between 0.250 inches and 0.320 inches

Body Width:

0.250 inches

Body Height:

0.438 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Style:

Round

Actuator Diameter:

0.125 inches

Actuator Height:

0.093 inches

Actuator Free Position Height:

0.437 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.012 overtravel inches and 0.012 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 10.000 amperes resistive ac

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0