

View Online at <https://aerobasegroup.com/nsn/5930-01-027-5388>

**Thread Class:**

2b 2nd mounting facility

**Thread Length:**

0.062 inches 1st mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

7.470 inches

**Shaft Length:**

2.470 inches single actuator

**Overall Diameter:**

3.750 inches

**Individual Section Quantity:**

8

**Knob Manufacturer Code:**

82121

**Knob Manufacturer Part Number:**

101605a-2a

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

3 each section rear

**Throw Quantity:**

3 each section rear

**Mounting Facility Circle Radius:**

3.250 inches 2nd mounting facility

**Mounting Method:**

Threaded hole 2nd mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

24 2nd mounting facility

**Thread Size:**

0.625 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

30.0 dc at sea level

**Mounting Facility Pattern:**

Four position circular 2nd mounting facility

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Rectangular/square, threaded hole single actuator

**Square Shaft Size:**

0.250 inches single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

7.5 amperes resistive load ac at sea level

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef 1st mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0