NSN 5930-01-027-5388

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-027-5388
Thread Class:
2b 2nd mounting facility
Thread Length:
0.062 inches 1st mounting facility
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
7.470 inches
Shaft Length:
2.470 inches single actuator
Overall Diameter:
3.750 inches
Individual Section Quantity:
8
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
101605a-2a
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
3 each section rear
Throw Quantity:
3 each section rear
Mounting Facility Circle Radius:
3.250 inches 2nd mounting facility
Mounting Method:
Threaded hole 2nd mounting facility
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):

24 2nd mounting facility

Thread Size:

0.625 inches 1st mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Mounting Facility Pattern:

Four position circular 2nd mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

NSN 5930-01-027-5388 Rotary Switch - Page 2 of 2



Square Shaft Size:	
0.250 inches single actuator	
Terminal Type:	
Tab w/screw	
Contact Switching Action:	
Breaks before makes each section rear	
Switch Actuator Positioning Increment:	
30.0 degrees single actuator	
Switch Actuator Stop Device Type:	
Adjustable stop single actuator	
Contact Load Current Rating:	
7.5 amperes resistive load ac at sea level	
Precious Material And Location:	
Contact surfaces silver	
Precious Material:	
Silver	
Style Designator:	
Tap, circular, bushing mount	
Thread Series Designator:	
Unef 1st mounting facility	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	

A052b0