## NSN 5930-01-027-6533

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-027-6533

Body Style:
Hole mount
Hazardous Locations/environmental Protection:
Moisture resistant
Center To Center Distance Between Mounting Facilities Parallel To Width:
Between 0.295 inches and 0.305 inches
Body Length:
1.020 inches
Body Width:
Between 0.575 inches and 0.585 inches
Body Height:
Between 0.575 inches and 0.585 inches
Actuator Length:
Between 0.205 inches and 0.215 inches
Actuator Style:
Rectangular
Actuator Height:
0.450 inches
Actuator Width:
Between 0.155 inches and 0.165 inches
Maximum Voltage Rating In Volts:
100.0 dc
Inclosure Type:
Hermetically sealed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
500.000 milliamperes resistive dc
Special Features:
Actuator includes shift lock, mtg holes diagonally spaced 0.300 in. By 0.400 in. Centers
Terminal Type And Quantity:
2 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Na

No

## NSN 5930-01-027-6533

Push Switch - Page 2 of 2



Fiig:

A053a0