

View Online at <https://aerobasegroup.com/nsn/5930-01-027-8177>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Bushing Length:

0.470 inches

Body Length:

0.575 inches

Body Width:

0.535 inches

Body Height:

0.640 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.800 inches and 0.850 inches

Actuator Width:

0.300 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Actuator Color:

White single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0