

View Online at <https://aerobasegroup.com/nsn/5930-01-027-8178>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Bushing Length:

0.320 inches

Body Length:

0.510 inches

Body Width:

0.310 inches

Body Height:

0.400 inches

Case Material:

Plastic

Actuator Style:

Rectangular

Actuator Height:

0.410 inches

Actuator Width:

0.200 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

125.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

6.000 amperes resistive dc and 2.000 amperes inductive dc and 6.000 amperes resistive ac and 2.000 amperes inductive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0