NSN 5930-01-027-9519

Rotary Switch - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5930-01-027-9519

2b 2nd mounting facility Thread Length: 0.375 inches 1st mounting facility **Hazardous Locations/environmental Protection:** Watertight **Overall Length:** 4.407 inches **Overall Height:** 2.562 inches **Overall Width:** 2.562 inches **Individual Section Quantity: Knob Manufacturer Code:** 82121 **Knob Manufacturer Part Number:** 105605a-2a **Knob Specificationial Markings:** White arrow symbol **Longest Horizontal Distance Between Mounting Centers:** 2.312 inches 2nd mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.312 inches 2nd mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section rear **Throw Quantity:** 3 each section front **Mounting Method:** Threaded bushing 1st mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 32 1st mounting facility **Thread Size:** 0.469 inches 1st mounting facility **Contact Voltage Rating In Volts:** 125.0 ac at sea level

Switch Actuator Momentary Position:

Clockwise single actuator

NSN 5930-01-027-9519

Rotary Switch - Page 2 of 2



Mounting Facility Pattern: Four position rectangular 2nd mounting facility **Switch Actuator Indexing Position Quantity:** 4 single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Breaks before makes each section front **Switch Actuator Positioning Increment:** 90.0 degrees single actuator **Contact Load Current Rating:** 10.0 amperes resistive load ac at sea level **Style Designator:** Tap, circuit selector **Thread Series Designator:** Uns 1st mounting facility Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A052b0