## NSN 5930-01-028-1041

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-028-1041

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Body Length:
0.781 inches
Body Width: 0.250 inches
Body Height:
0.359 inches
Unthreaded Mounting Hole Diameter:
Between 0.087 inches and 0.090 inches
Actuator Style:
Leaf
Actuator Width:
0.125 inches
Actuator Free Position Height:
Between 0.406 inches and 0.437 inches
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
3.0 grams
Switch Actuating Force:
20.0 grams
Actuator Movement:
0.438 pretravel inches and 0.050 overtravel inches and 0.050 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
10.100 amperes resistive ac
Terminal Type And Quantity:
3 quick disconnect, female
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5930-01-028-1041

Sensitive Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0