

View Online at <https://aerobasegroup.com/nsn/5930-01-028-3895>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Body Diameter:

1.100 inches

Bushing Length:

0.470 inches

Body Length:

1.100 inches

Actuator Style:

Round

Actuator Diameter:

0.430 inches

Actuator Height:

1.180 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Position-locking Relationship:

Up position locked in and down position locked in and center position locked out

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

6 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 4.000 amperes motor dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac and 3.300 amperes motor ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

18 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0