

View Online at <https://aerobasegroup.com/nsn/5930-01-028-8466>

**Thread Class:**

3b all pressure connection

**Thread Length:**

0.656 inches all pressure connection

**Overall Length:**

3.600 inches

**Overall Height:**

2.800 inches

**Overall Width:**

3.540 inches

**Unthreaded Mounting Hole Diameter:**

0.210 inches

**Distance Between Mounting Facility Centers:**

3.000 inches

**Pressure Switch Type:**

Differential

**Operating Temperature Rating:**

Between -67.0 degrees fahrenheit and 160.0 degrees fahrenheit

**Mounting Method:**

Flange and unthreaded hole

**Features Provided:**

Hermetically sealed case

**Thready Qty Per Inch (tpi):**

20 all pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

180.00 pounds per square inch gage

**Thread Size:**

0.438 inches all pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Sensing Element Burst Pressure:**

240.00 pounds per square inch gage

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

5.0 amperes resistive load single voltage and 3.0 amperes inductive load single voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

85.00 actuation point pounds per square inch and 60.00 deactuation point pounds per square inch and 25.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

28.0 ac at sea level single voltage

**Pressure Connector Type:**

Plain, threaded internal all connections

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical w/mounting lugs

**Thread Series Designator:**

Unf all pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0