

View Online at <https://aerobasegroup.com/nsn/5930-01-029-0950>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Flame resistant

Bushing Length:

0.380 inches

Body Length:

1.050 inches

Body Width:

0.780 inches

Actuator Style:

Round

Actuator Diameter:

0.230 inches

Actuator Height:

0.800 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained and left position maintained and right position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

0.920 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 four throw, normally open, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac

Precious Material And Location:

Internal contacts silver and internal contact surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0