

View Online at <https://aerobasegroup.com/nsn/5930-01-029-0950>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Flame resistant

**Bushing Length:**

0.380 inches

**Body Length:**

1.050 inches

**Body Width:**

0.780 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.230 inches

**Actuator Height:**

0.800 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained and left position maintained and right position maintained

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

0.920 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 four throw, normally open, momentary action single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac

**Precious Material And Location:**

Internal contacts silver and internal contact surfaces gold

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

12 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0