## NSN 5930-01-029-0951

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-029-0951
Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Dustproof and moisture resistant
Case Material:
Metal
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.310 inches
Housing Diameter:
1.500 inches
Housing Length:
1.860 inches
Housing Bushing Length:
0.750 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Aircraft, eagle f-15
Inclosure Type:
Fully enclosed
Mounting Method:
Integral
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
144.0 inch-ounces
Criticality Code Justification:
Feat
Switch Actuating Force:
192.0 inch-ounces
Actuator Movement:
13.0 pretravel degrees and 32.0 overtravel degrees and 4.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 5.000
amperes inductive ac

Special Features:

Weapon system essential

## NSN 5930-01-029-0951

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:
6 wire lead
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0