# NSN 5930-01-029-3034

Push Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-029-3034

# **Body Style:**

Panel mount

# Hazardous Locations/environmental Protection:

Moisture proof

**Body Length:** 

3.060 inches

#### **Body Width:**

0.740 inches

# **Body Height:**

0.990 inches

**Case Material:** 

# Metal

**Actuator Color:** 

#### Red single actuator

**Illuminated Actuator Color:** 

Red single actuator

#### Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

## **End Application:**

Sturgeon class ssn (637), submarine (ssn) fire control sys, submarine acoustic sonar systems, submarine armament and fire control systems, sonar, an/bsy- (v), los angeles class ssn (688)

Inclosure Type:

Fully enclosed

**Features Provided:** 

Rfi shielding

#### **Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

## Criticality Code Justification:

Feat

## Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac

## **Special Features:**

Horizontal split display; weapon system essential

## **Terminal Type And Quantity:**

9 tab, solder lug

## Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A053a0