NSN 5930-01-029-3564

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-029-3564

Body Style:
Hole mounted
Overall Length:
0.781 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Overall Height:
0.713 inches
Overall Width:
0.250 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.359 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Style:
Round
Actuator Diameter:
0.092 inches
Actuator Height:
0.110 inches
Actuator Free Position Height:
0.375 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Los angeles class (688) ssn, strugeion class (637) ssn mk93 fire control system
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
1.0 ounces

Feat

Criticality Code Justification:

NSN 5930-01-029-3564

Sensitive Switch - Page 2 of 2

A053a0



Switch Actuating Force:
5.0 ounces
Actuator Movement:
Between 0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes
inductive ac and 1.500 amperes lamp ac
Special Features:
Weapon system essential
Precious Material And Location:
Contacts gold
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig: