

View Online at <https://aerobasegroup.com/nsn/5930-01-029-3564>

Body Style:

Hole mounted

Overall Length:

0.781 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Overall Height:

0.713 inches

Overall Width:

0.250 inches

Body Length:

0.781 inches

Body Width:

0.250 inches

Body Height:

0.359 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Style:

Round

Actuator Diameter:

0.092 inches

Actuator Height:

0.110 inches

Actuator Free Position Height:

0.375 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Los angeles class (688) ssn, strugeion class (637) ssn mk93 fire control system

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

Special Features:

Weapon system essential

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0