NSN 5930-01-029-4130

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-029-4130

Thread Class:

3a single pressure connection

Overall Length:

3.147 inches

Outside Diameter:

0.900 inches single connection

Body Length:

2.100 inches

Overall Diameter:

0.900 inches

Pressure Switch Type:

Gage

Operating Tempurature Rating:

260.0 degrees fahrenheit

Mounting Method:

Input port

Features Provided:

Electrical box connector

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

585.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Sensing Element Burst Pressure:

795.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

10.0 milliamperes inductive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

130.00 actuation point pounds per square inch gage and 90.00 deactuation point pounds per square inch gage and 40.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

NSN 5930-01-029-4130

Pressure Switch - Page 2 of 2



Media For Which Designed:
Gas
Style Designator:
Cylindrical
Thread Series Designator:
Unf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0