

View Online at <https://aerobasegroup.com/nsn/5930-01-029-4291>

Hazardous Locations/environmental Protection:

Dustproof and explosion proof and moisture proof

Overall Length:

Between 1.240 inches and 1.260 inches

Overall Height:

Between 0.607 inches and 0.630 inches

Body Diameter:

Between 0.610 inches and 0.630 inches

Body Height:

Between 0.367 inches and 0.390 inches

Unthreaded Mounting Hole Diameter:

Between 0.138 inches and 0.150 inches

Distance Between Mounting Facility Centers:

Between 0.928 inches and 0.948 inches

End Application:

Console wn cont sta 16603

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

300.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

6.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 1.0 amperes lamp load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

105.00 actuation point degrees fahrenheit and 85.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Media For Which Designed:

Gas

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0