NSN 5930-01-029-4850

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-029-4850

Overall Length:
4.875 inches
Overall Height:
3.500 inches
Overall Width:
2.625 inches
Body Height:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Distance Between Mounting Facility Centers:
5.250 inches
Capillary Tube Length:
120.0 inches
Bulb Length:
8.250 inches
Bulb Diameter:
0.688 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, two positions momentary
Terminal Type:
Screw
Contact Load Current Rating:
Contact Load Current Nating.
9.6 amperes resistive load fourth voltage
-
9.6 amperes resistive load fourth voltage
9.6 amperes resistive load fourth voltage Contact Adjustability:
9.6 amperes resistive load fourth voltage Contact Adjustability: Deactuation point adjustable and actuation point adjustable
9.6 amperes resistive load fourth voltage Contact Adjustability: Deactuation point adjustable and actuation point adjustable Contact Adjustment Range:

Contact Voltage Rating In Volts: 550.0 dc at sea level third voltage

NSN 5930-01-029-4850

Thermostatic Switch - Page 2 of 2



Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0