# NSN 5930-01-029-4850

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-029-4850

| Overall Longth  |
|---|
| Overall Length:   |
| 4.875 inches  |
| Overall Height:   |
| 3.500 inches  |
| Overall Width:  |
| 2.625 inches  |
| Body Height:  |
| 2.750 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.281 inches  |
| Distance Between Mounting Facility Centers:   |
| 5.250 inches  |
| Capillary Tube Length:  |
| 120.0 inches  |
| Bulb Length:  |
| 8.250 inches  |
| Bulb Diameter:  |
| 0.688 inches  |
| Tempurature Sensing Element Type:   |
| Capillary tube-bulb   |
| Mounting Method:  |
| Unthreaded hole   |
| Features Provided:  |
| Electrical access port  |
| Contact Action Stimulus:  |
| Increase  |
| Mounting Facility Pattern:  |
| Two position in-line  |
| Nonpile-up Contact Arrangement:   |
| 1 pole, double throw, two positions momentary   |
| Terminal Type:  |
| Screw   |
| Contact Load Current Rating:  |
| 9.6 amperes resistive load fourth voltage   |
| Contact Adjustability:  |
| Deactuation point adjustable and actuation point adjustable   |
| Contact Adjustment Range:   |
| +25.00/+90.00 actuation point degrees fahrenheit and +25.00/+90.00 deactuation point degrees fahrenheit |
| Contact Adjustment Type:  |
| External deactuation point screw and external actuation point screw                                     |
| Contact Voltage Rating In Volts:  |
| 550.0 dc at sea level third voltage   |
|   |

# NSN 5930-01-029-4850

Thermostatic Switch - Page 2 of 2



#### Media For Which Designed:

Gas or liquid

#### Style Designator:

Rectangular

Shelf Life:

N/a

### Unit Of Measure:

---

### Demilitarization:

No

Fiig:

A048b0