

View Online at <https://aerobasegroup.com/nsn/5930-01-029-6482>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.872 inches and 0.878 inches

**Body Length:**

Between 1.079 inches and 1.109 inches

**Body Width:**

Between 0.385 inches and 0.415 inches

**Body Height:**

Between 0.610 inches and 0.640 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.113 inches and 0.116 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.403 inches and 0.409 inches

**Actuator Length:**

0.775 inches

**Actuator Style:**

Leaf

**Actuator Width:**

Between 0.155 inches and 0.185 inches

**Actuator Free Position Height:**

Between 0.167 inches and 0.221 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

6.0 grams

**Switch Actuating Force:**

55.0 grams

**Actuator Movement:**

Between 0.080 pretravel inches and 0.060 overtravel inches and 0.022 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

0.250 amperes resistive dc and 10.000 amperes resistive ac

**Terminal Type And Quantity:**

3 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0