

View Online at <https://aerobasegroup.com/nsn/5930-01-029-6482>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Corrosion resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.872 inches and 0.878 inches

Body Length:

Between 1.079 inches and 1.109 inches

Body Width:

Between 0.385 inches and 0.415 inches

Body Height:

Between 0.610 inches and 0.640 inches

Unthreaded Mounting Hole Diameter:

Between 0.113 inches and 0.116 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.403 inches and 0.409 inches

Actuator Length:

0.775 inches

Actuator Style:

Leaf

Actuator Width:

Between 0.155 inches and 0.185 inches

Actuator Free Position Height:

Between 0.167 inches and 0.221 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

6.0 grams

Switch Actuating Force:

55.0 grams

Actuator Movement:

Between 0.080 pretravel inches and 0.060 overtravel inches and 0.022 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

0.250 amperes resistive dc and 10.000 amperes resistive ac

Terminal Type And Quantity:

3 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0