

View Online at <https://aerobasegroup.com/nsn/5930-01-029-7736>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.907 inches and 0.927 inches

Body Length:

Between 3.010 inches and 3.070 inches

Body Width:

Between 0.990 inches and 1.010 inches

Body Height:

Between 1.720 inches and 1.780 inches

Unthreaded Mounting Hole Diameter:

0.1085 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.320 inches and 0.340 inches

Actuator Height:

Between 0.710 inches and 0.790 inches

Actuator Free Position Height:

Between 1.490 inches and 1.510 inches

Maximum Voltage Rating In Volts:

800.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 9.0 ounces and 13.0 ounces

Actuator Movement:

Between 0.219 overtravel inches and 0.002 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

0.250 amperes resistive dc and 2.000 amperes resistive ac

Special Features:

250 degrees f max, gray painted enclosure

Thread Series Designator:

Unc

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0