

View Online at <https://aerobasegroup.com/nsn/5930-01-029-7736>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.907 inches and 0.927 inches

**Body Length:**

Between 3.010 inches and 3.070 inches

**Body Width:**

Between 0.990 inches and 1.010 inches

**Body Height:**

Between 1.720 inches and 1.780 inches

**Unthreaded Mounting Hole Diameter:**

0.1085 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.320 inches and 0.340 inches

**Actuator Height:**

Between 0.710 inches and 0.790 inches

**Actuator Free Position Height:**

Between 1.490 inches and 1.510 inches

**Maximum Voltage Rating In Volts:**

800.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 9.0 ounces and 13.0 ounces

**Actuator Movement:**

Between 0.219 overtravel inches and 0.002 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

0.250 amperes resistive dc and 2.000 amperes resistive ac

**Special Features:**

250 degrees f max, gray painted enclosure

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0