NSN 5930-01-029-9950

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-029-9950

Overall Length:
4.875 inches
Overall Height:
4.938 inches
Overall Width:
2.625 inches
Body Length:
4.875 inches
Capillary Tube Length:
72.0 inches
Bulb Length:
3.625 inches
Bulb Diameter:
0.688 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
1.750 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Operating Tempurature Rating:
437.0 degrees fahrenheit
Mounting Method:
Bracket
Features Provided:
Capillary tube end seal connection
Contact Action Stimulus:
Decrease
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab w/screw
Contact Load Current Rating:
3.2 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+300.00/+400.00 actuation point degrees fahrenheit and +298.00/+395.00 deactuation point degrees fahrenheit

NSN 5930-01-029-9950

Thermostatic Switch - Page 2 of 2



Contact	Adjustment	Type:
---------	------------	-------

External deactuation point knob and external actuation point knob

Contact Voltage Rating In Volts:

550.0 ac at sea level first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0