

View Online at <https://aerobasegroup.com/nsn/5930-01-029-9959>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.880 inches

Body Length:

1.090 inches

Body Width:

0.400 inches

Body Height:

0.630 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.410 inches

Actuator Length:

2.340 inches

Actuator Style:

Leaf

Actuator Free Position Height:

Between 0.530 inches and 0.670 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

0.070 ounces

Switch Actuating Force:

0.710 ounces

Actuator Movement:

Between 0.200 pretravel inches and 0.160 overtravel inches and 0.055 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 10.000 amperes resistive ac

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0