## NSN 5930-01-030-1522

Thermostatic Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-030-1522

| Overall Width:         |  |
|------------------------|--|
| 2.060 inches           |  |
| Body Length:           |  |
| 2.090 inches           |  |
| Unthreaded Mountin     | ng Hole Diameter:  |
| Between 0.200 inches   | s and 0.220 inches   |
| Longest Horizontal     | Distance Between Mounting Centers:                                     |
| 2.656 inches           |  |
| Longest Vertical Dis   | tance Between Mounting Centers:  |
| 0.875 inches           |  |
| Tempurature Sensin     | g Element Type:  |
| Thermocouple           |  |
| Operating Tempurat     | ure Rating:  |
| Between -65.0 degree   | es fahrenheit and 250.0 degrees fahrenheit                             |
| Mounting Method:       |  |
| Bracket and unthread   | ed hole  |
| Features Provided:     |  |
| Tamper proof cap       |  |
| Contact Action Stim    | ulus:  |
| Increase               |  |
| Mounting Facility Pa   | ittern:  |
| Four position rectang  | ular   |
| Terminal Type:         |  |
| Connector, receptacl   | e  |
| Contact Adjustabilit   | y:   |
| Actuation point adjust | able, preset and deactuation point not adjustable                      |
| Contact Adjustment     | Туре:  |
| External actuation poi | int screw  |
| Contact Stimulus Ra    | ating:   |
| 1425.00 actuation poi  | nt degrees fahrenheit and 1300.00 deactuation point degrees fahrenheit |
| Media For Which De     | signed:  |
| Gas                    |  |
| Shelf Life:            |  |
| N/a                    |  |
| Unit Of Measure:       |  |
|                        |  |
| Demilitarization:      |  |
| No                     |  |
| Fiig:                  |  |
| A048b0                 |  |