NSN 5930-01-030-2023

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-030-2023

| Hazardous Locations/environmental Protection: |
|---|
| Dustproof |
| Overall Length: |
| 1.190 inches |
| Overall Height: |
| 0.295 inches |
| Overall Width: |
| 0.350 inches |
| Individual Section Quantity: |
| 10 |
| Operating Tempurature Range: |
| -40.0/+85.0 degrees celsius |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 each section front |
| Mounting Method: |
| Printed circuit single mounting facility |
| Contact Voltage Rating In Volts: |
| 60.0 dc at sea level |
| Rotor Through Connection Quantity: |
| 1 each section |
| Switch Actuator Indexing Position Quantity: |
| 10 single actuator |
| Terminal Type: |
| Printed circuit |
| Contact Switching Action: |
| Breaks before makes each section front |
| Switch Actuator Stop Device Type: |
| Adjustable stop single actuator |
| Contact Load Current Rating: |
| 0.500 amperes resistive load dc at sea level |
| Special Features: |
| Snap open cover |
| Precious Material And Location: |
| Contacts and terminals gold |
| Precious Material: |
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5930-01-030-2023

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0