NSN 5930-01-030-3031

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-030-3031

view offilite at https://aerobasegroup.com/nsi//0550-01-050-5051
Thread Class:
2a
Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Shock resistant and vibration resistant
Overall Length:
0.745 inches
Overall Height:
3.120 inches
Overall Width:
0.745 inches
Body Diameter:
0.745 inches
Bushing Length:
0.410 inches
Case Material:
Metal
Actuator Diameter:
0.375 inches
Actuator Height:
0.560 inches
Maximum Voltage Rating In Volts:
125.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Features Provided:
Holding solenoid
Thready Qty Per Inch (tpi):
32
Thread Size:
0.562 inches
Nonpile-up Contact Arrangement:
6 pole, single throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
2.000 amperes resistive dc and 0.500 amperes inductive dc and 2.000 amperes resistive ac and 0.500 amperes inductive ac
Thread Series Designator:
Un

Terminal Type And Quantity:

14 tab, solder lug and 2 wire lead

NSN 5930-01-030-3031

Push Switch - Page 2 of 2



-				
٠.	hΔ	Iŧ.	ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0