

View Online at <https://aerobasegroup.com/nsn/5930-01-030-3031>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Shock resistant and vibration resistant

**Overall Length:**

0.745 inches

**Overall Height:**

3.120 inches

**Overall Width:**

0.745 inches

**Body Diameter:**

0.745 inches

**Bushing Length:**

0.410 inches

**Case Material:**

Metal

**Actuator Diameter:**

0.375 inches

**Actuator Height:**

0.560 inches

**Maximum Voltage Rating In Volts:**

125.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Holding solenoid

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.562 inches

**Nonpile-up Contact Arrangement:**

6 pole, single throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 0.500 amperes inductive dc and 2.000 amperes resistive ac and 0.500 amperes inductive ac

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

14 tab, solder lug and 2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0