NSN 5930-01-030-4723

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-030-4723

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
5.376 inches
Overall Height:
2.906 inches
Overall Width:
2.813 inches
Unthreaded Mounting Hole Diameter:
0.221 inches single mounting facility
Individual Section Quantity:
2
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
В
Longest Horizontal Distance Between Mounting Centers:
2.000 inches single mounting facility
Shortest Horizontal Distance Between Mounting Centers:
1.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.188 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section rear
Throw Quantity:
7 each section rear
Mounting Method:
Unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
600.0 ac at sea level
Switch Actuator Momentary Position:
Counterclockwise single actuator
Mounting Facility Pattern:
Isosceles triangle single mounting facility
Switch Actuator Indexing Position Quantity:
8 single actuator
Criticality Code Justification:

Feat

NSN 5930-01-030-4723Rotary Switch - Page 2 of 2



Terminal Type:	
Tab w/screw	
Contact Switching Action:	
Breaks before makes each section rear	
Switch Actuator Positioning Increment:	
45.0 degrees single actuator	
Switch Actuator Stop Device Type:	
Adjustable stop single actuator	
Contact Load Current Rating:	
20.0 amperes resistive load ac at sea level	
Special Features:	
Item must comply with requirements of desc production standard no. L02254, for navy nuclear propulsion plant only	
Style Designator:	
Tap, circuit selector	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Fiig:	
A052b0	