NSN 5930-01-030-6260

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-030-6260

6.230 inches Overall Height: 3.100 inches Overall Width: 4.750 inches Unthreaded Mounting Hole Diameter: 0.265 inches Longest Horizontal Distance Between Mounting Centers: 4.250 inches Longest Vertical Distance Between Mounting Centers: 3.100 inches Pressure Switch Type: Gage Mounting Method: Unthreaded hole Features Provided: Electrical access port Thready Qty Per Inch (tpi): 14 single pressure connection Contact Action Stimulus: Increase Prior Pressure: 4500.00 pounds per square inch gage Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	
Overall Height: 3.100 inches Overall Width: 4.750 inches Unthreaded Mounting Hole Diameter: 0.265 inches Longest Horizontal Distance Between Mounting Centers: 4.250 inches Longest Vertical Distance Between Mounting Centers: 3.100 inches Pressure Switch Type: Gage Mounting Method: Unthreaded hole Features Provided: Electrical access port Thready Qty Per Inch (tpi): 14 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 4500.00 pounds per square inch gage Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	Overall Length:
3.100 inches Overall Width: 4.750 inches Unthreaded Mounting Hole Diameter: 0.265 inches Longest Horizontal Distance Between Mounting Centers: 4.250 inches Longest Vertical Distance Between Mounting Centers: 3.100 inches Pressure Switch Type: Gage Mounting Method: Unthreaded hole Features Provided: Electrical access port Thready Qty Per Inch (tpi): 14 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 4500.00 pounds per square inch gage Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	
Overall Width: 4.750 inches Unthreaded Mounting Hole Diameter: 0.265 inches Longest Horizontal Distance Between Mounting Centers: 4.250 inches Longest Vertical Distance Between Mounting Centers: 3.100 inches Pressure Switch Type: Gage Mounting Method: Unthreaded hole Features Provided: Electrical access port Thready Oty Per Inch (tpl): 14 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 4500.00 pounds per square inch gage Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	-
4.750 inches Unthreaded Mounting Hole Diameter: 0.265 inches Longest Horizontal Distance Between Mounting Centers: 4.250 inches Longest Vertical Distance Between Mounting Centers: 3.100 inches Pressure Switch Type: Gage Mounting Method: Unthreaded hole Features Provided: Electrical access port Thready day Per Inch (tpi): 14 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 4500.00 pounds per square inch gage Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	
Unthreaded Mounting Hole Diameter: 0.265 inches Longest Horizontal Distance Between Mounting Centers: 4.250 inches Longest Vertical Distance Between Mounting Centers: 3.100 inches Pressure Switch Type: Gage Mounting Method: Unthreaded hole Features Provided: Electrical access port Thready Qty Per Inch (tpl): 14 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 4500.00 pounds per square inch gage Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	Overall Width:
Longest Horizontal Distance Between Mounting Centers: 4.250 inches Longest Vertical Distance Between Mounting Centers: 3.100 inches Pressure Switch Type: Gage Mounting Method: Unthreaded hole Features Provided: Electrical access port Thready Qty Per Inch (tpi): 14 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 4500.00 pounds per square inch gage Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	
Longest Horizontal Distance Between Mounting Centers: 4.250 inches Longest Vertical Distance Between Mounting Centers: 3.100 inches Pressure Switch Type: Gage Mounting Method: Unthreaded hole Electrical access port Thready Qty Per Inch (tpi): 14 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 4500.00 pounds per square inch gage Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	Unthreaded Mounting Hole Diameter:
4.250 inches Longest Vertical Distance Between Mounting Centers: 3.100 inches Pressure Switch Type: Gage Mounting Method: Unthreaded hole Features Provided: Electrical access port Thready Qty Per Inch (tpi): 14 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 4500.00 pounds per square inch gage Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	0.265 inches
Longest Vertical Distance Between Mounting Centers: 3.100 inches Pressure Switch Type: Gage Mounting Method: Unthreaded hole Features Provided: Electrical access port Thready Qty Per Inch (tpi): 14 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 4500.00 pounds per square inch gage Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	Longest Horizontal Distance Between Mounting Centers:
3.100 inches Pressure Switch Type: Gage Mounting Method: Unthreaded hole Features Provided: Electrical access port Thready Qty Per Inch (tpi): 14 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 4500.00 pounds per square inch gage Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	4.250 inches
Pressure Switch Type: Gage Mounting Method: Unthreaded hole Features Provided: Electrical access port Thready Qty Per Inch (tpi): 14 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 4500.00 pounds per square inch gage Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	Longest Vertical Distance Between Mounting Centers:
Mounting Method: Unthreaded hole Features Provided: Electrical access port Thready Qty Per Inch (tpi): 14 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 4500.00 pounds per square inch gage Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	3.100 inches
Mounting Method: Unthreaded hole Features Provided: Electrical access port Thready Qty Per Inch (tpi): 14 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 4500.00 pounds per square inch gage Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	Pressure Switch Type:
Unthreaded hole Features Provided: Electrical access port Thready Qty Per Inch (tpi): 14 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 4500.00 pounds per square inch gage Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	Gage
Features Provided: Electrical access port Thready Qty Per Inch (tpi): 14 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 4500.00 pounds per square inch gage Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	Mounting Method:
Electrical access port Thready Qty Per Inch (tpi): 14 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 4500.00 pounds per square inch gage Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	Unthreaded hole
Thready Qty Per Inch (tpi): 14 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 4500.00 pounds per square inch gage Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	Features Provided:
14 single pressure connection Contact Action Stimulus: Increase Proof Pressure: 4500.00 pounds per square inch gage Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	Electrical access port
Contact Action Stimulus: Increase Proof Pressure: 4500.00 pounds per square inch gage Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	Thready Qty Per Inch (tpi):
Increase Proof Pressure: 4500.00 pounds per square inch gage Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	14 single pressure connection
Proof Pressure: 4500.00 pounds per square inch gage Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	Contact Action Stimulus:
4500.00 pounds per square inch gage Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	Increase
Thread Size: 0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	Proof Pressure:
0.750 inches single pressure connection Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	4500.00 pounds per square inch gage
Mounting Facility Pattern: Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	Thread Size:
Four position rectangular Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	0.750 inches single pressure connection
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	Mounting Facility Pattern:
1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	Four position rectangular
Terminal Type: Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	Nonpile-up Contact Arrangement:
Screw Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	1 pole, double throw, one position momentary
Contact Load Current Rating: 20.0 milliamperes resistive load second voltage Contact Adjustability:	Terminal Type:
20.0 milliamperes resistive load second voltage Contact Adjustability:	Screw
Contact Adjustability:	Contact Load Current Rating:
	20.0 milliamperes resistive load second voltage
Deactuation point adjustable and actuation point adjustable	Contact Adjustability:
	Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:	Contact Adjustment Range:
+60.00/+225.00 actuation point pounds per square inch gage and +45.00/+176.00 deactuation point pounds per square inch gage	
Contact Adjustment Type:	
External deactuation point screw and external actuation point screw	External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts: 480.0 ac at sea level first voltage

NSN 5930-01-030-6260

Pressure Switch - Page 2 of 2



Pressure Connector Type:
Plain, threaded internal single connection
Media For Which Designed:
Gas
Thread Series Designator:
Npt single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0