

View Online at <https://aerobasegroup.com/nsn/5930-01-030-6260>

Overall Length:

6.230 inches

Overall Height:

3.100 inches

Overall Width:

4.750 inches

Unthreaded Mounting Hole Diameter:

0.265 inches

Longest Horizontal Distance Between Mounting Centers:

4.250 inches

Longest Vertical Distance Between Mounting Centers:

3.100 inches

Pressure Switch Type:

Gage

Mounting Method:

Unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

14 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch gage

Thread Size:

0.750 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

20.0 milliamperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+60.00/+225.00 actuation point pounds per square inch gage and +45.00/+176.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0