

View Online at <https://aerobasegroup.com/nsn/5930-01-031-4612>

Thread Class:

2a

Body Style:

Bushing mount

Bushing Length:

Between 0.342 inches and 0.362 inches

Body Length:

0.850 inches

Body Width:

Between 0.495 inches and 0.505 inches

Body Height:

0.415 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

Between 0.114 inches and 0.116 inches

Actuator Height:

Between 0.390 inches and 0.410 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

0.571 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0