

View Online at <https://aerobasegroup.com/nsn/5930-01-031-4616>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.188 inches

**Body Length:**

0.500 inches

**Body Width:**

0.200 inches

**Body Height:**

0.350 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.088 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.063 inches

**Actuator Height:**

0.050 inches

**Actuator Free Position Height:**

0.320 inches

**Maximum Voltage Rating In Volts:**

125.0 ac and 28.0 dc

**End Application:**

Spruance class dd (963), nimitz class cvn, kidd class ddg, ticonderoga class cg (47), oliver perry class ffg

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, two positions momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

Between 2.5 ounces and 5.0 ounces

**Actuator Movement:**

Between 0.020 pretravel inches and 0.004 overtravel inches and 0.003 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 500.000 milliamperes inductive dc and 1.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

3 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0