

View Online at <https://aerobasegroup.com/nsn/5930-01-031-4616>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.188 inches

Body Length:

0.500 inches

Body Width:

0.200 inches

Body Height:

0.350 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Style:

Round

Actuator Diameter:

0.063 inches

Actuator Height:

0.050 inches

Actuator Free Position Height:

0.320 inches

Maximum Voltage Rating In Volts:

125.0 ac and 28.0 dc

End Application:

Spruance class dd (963), nimitz class cvn, kidd class ddg, ticonderoga class cg (47), oliver perry class ffg

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Switch Release Force:

1.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

Between 2.5 ounces and 5.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.004 overtravel inches and 0.003 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc and 1.000 amperes resistive ac

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0