

View Online at <https://aerobasegroup.com/nsn/5930-01-031-6370>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Corrosion resistant

Bushing Length:

0.875 inches

Body Length:

0.515 inches

Body Width:

0.750 inches

Actuator Style:

Round

Actuator Diameter:

0.219 inches

Actuator Height:

0.312 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Switch Release Force:

24.0 ounces

Switch Actuating Force:

48.0 ounces

Actuator Movement:

Between 0.047 pretravel inches and 0.250 overtravel inches and 0.015 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0