

View Online at <https://aerobasegroup.com/nsn/5930-01-031-6370>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Bushing Length:**

0.875 inches

**Body Length:**

0.515 inches

**Body Width:**

0.750 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.219 inches

**Actuator Height:**

0.312 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, two positions momentary single switch unit

**Switch Release Force:**

24.0 ounces

**Switch Actuating Force:**

48.0 ounces

**Actuator Movement:**

Between 0.047 pretravel inches and 0.250 overtravel inches and 0.015 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0