## NSN 5930-01-031-9727

**Hazardous Locations/environmental Protection:** 

Push Switch - Page 1 of 2

Explosion proof and humidity resistant

**Body Style:**Panel mounted

Overall Length: 3.635 inches Overall Height: 0.750 inches



View Online at https://aerobasegroup.com/nsn/5930-01-031-9727

Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Actuator Length:
0.625 inches
Actuator Style:
Rectangular
Actuator Height:
0.100 inches
Actuator Width:
0.625 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Green single actuator and white single actuator
Actuator Inscription:
Valve single actuator
Maximum Voltage Rating In Volts:
28.0 dc
Mounting Surface To Terminal End Distance:
3.535 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Full display lens and lamp holder
Nonpile-up Contact Arrangement:
3 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc

## NSN 5930-01-031-9727

Push Switch - Page 2 of 2



Precious Materia	I And Location:
------------------	-----------------

Contacts silver

**Terminal Type And Quantity:** 

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0