NSN 5930-01-031-9727

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Explosion proof and humidity resistant

Body Style:Panel mounted

Overall Length: 3.635 inches Overall Height: 0.750 inches



View Online at https://aerobasegroup.com/nsn/5930-01-031-9727

| Overall Width: |
|-------------------------------------------------------------------------------------|
| 0.750 inches |
| Body Width: |
| 0.750 inches |
| Body Height: |
| 0.750 inches |
| Actuator Length: |
| 0.625 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.100 inches |
| Actuator Width: |
| 0.625 inches |
| Actuator Color: |
| Black single actuator |
| Illuminated Actuator Color: |
| Green single actuator and white single actuator |
| Actuator Inscription: |
| Valve single actuator |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Mounting Surface To Terminal End Distance: |
| 3.535 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Full display lens and lamp holder |
| Nonpile-up Contact Arrangement: |
| 3 pole, double throw, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc |

NSN 5930-01-031-9727

Push Switch - Page 2 of 2



| Preci | ious | Material | And | Location: |
|-------|------|----------|-----|-----------|
|-------|------|----------|-----|-----------|

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0