# NSN 5930-01-031-9730

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-031-9730



# **Body Style:**

Panel mounted

#### Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

#### **Overall Length:**

3.635 inches

#### **Overall Height:**

0.750 inches

#### **Overall Width:**

0.750 inches

#### **Body Width:**

0.750 inches

#### **Body Height:**

0.750 inches

#### Case Material:

Metal

# Actuator Length:

0.531 inches

# Actuator Style:

Rectangular

#### Actuator Height:

0.100 inches

# Actuator Width:

0.531 inches

### Actuator Color:

Black single actuator

#### **Illuminated Actuator Color:**

Green single actuator

#### **Actuator Inscription:**

Off single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

## Mounting Surface To Terminal End Distance:

3.535 inches

#### Inclosure Type:

Fully enclosed

# **Mounting Method:**

Panel

#### **Features Provided:**

Full display lens

#### **Nonpile-up Contact Arrangement:**

3 pole, double throw, both positions maintained single switch unit

NSN 5930-01-031-9730

Push Switch - Page 2 of 2



# Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes

inductive ac and 1.000 amperes lamp ac

# **Precious Material And Location:**

Contacts silver

# **Terminal Type And Quantity:**

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

Fiig:

A053a0