

View Online at <https://aerobasegroup.com/nsn/5930-01-032-1150>

Hazardous Locations/environmental Protection:

Watertight

Overall Height:

2.813 inches

Body Diameter:

7.000 inches

Pressure Switch Type:

Differential

Mounting Method:

Input port

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

500.0 milliamperes resistive load fourth voltage

Contact Adjustability:

Deactuation point not adjustable, manual reset and actuation point adjustable

Contact Adjustment Range:

+300.00/+2500.00 actuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point screw with scale

Contact Stimulus Rating:

2200.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

240.0 dc at sea level third voltage

Pressure Connector Type:

Plain, threaded external single connection

Media For Which Designed:

Gas or liquid

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0