NSN 5930-01-032-1894

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-032-1894

Body Style: Hole mounted Hazardous Locations/environmental Protection: Dustproof Center To Center Distance Between Mounting Facilities Parallel To Length: 0.875 inches Body Length: 1.090 inches Body Width: 0.410 inches Body Height: 0.620 inches Case Material: Plastic Unthreaded Mounting Hole Diameter: 0.114 inches
Hazardous Locations/environmental Protection: Dustproof Center To Center Distance Between Mounting Facilities Parallel To Length: 0.875 inches Body Length: 1.090 inches Body Width: 0.410 inches Body Height: 0.620 inches Case Material: Plastic Unthreaded Mounting Hole Diameter:
Dustproof Center To Center Distance Between Mounting Facilities Parallel To Length: 0.875 inches Body Length: 1.090 inches Body Width: 0.410 inches Body Height: 0.620 inches Case Material: Plastic Unthreaded Mounting Hole Diameter:
Center To Center Distance Between Mounting Facilities Parallel To Length: 0.875 inches Body Length: 1.090 inches Body Width: 0.410 inches Body Height: 0.620 inches Case Material: Plastic Unthreaded Mounting Hole Diameter:
0.875 inches Body Length: 1.090 inches Body Width: 0.410 inches Body Height: 0.620 inches Case Material: Plastic Unthreaded Mounting Hole Diameter:
Body Length: 1.090 inches Body Width: 0.410 inches Body Height: 0.620 inches Case Material: Plastic Unthreaded Mounting Hole Diameter:
1.090 inches Body Width: 0.410 inches Body Height: 0.620 inches Case Material: Plastic Unthreaded Mounting Hole Diameter:
Body Width: 0.410 inches Body Height: 0.620 inches Case Material: Plastic Unthreaded Mounting Hole Diameter:
0.410 inches Body Height: 0.620 inches Case Material: Plastic Unthreaded Mounting Hole Diameter:
Body Height: 0.620 inches Case Material: Plastic Unthreaded Mounting Hole Diameter:
0.620 inches Case Material: Plastic Unthreaded Mounting Hole Diameter:
Case Material: Plastic Unthreaded Mounting Hole Diameter:
Plastic Unthreaded Mounting Hole Diameter:
Unthreaded Mounting Hole Diameter:
-
0.114 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.406 inches
Actuator Length:
1.340 inches
Actuator Style:
Roller arm
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Actuating Force:
22.0 grams
Actuator Movement:
Between 0.125 pretravel inches and 0.090 overtravel inches and 0.030 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive ac
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a

--

NSN 5930-01-032-1894

Sensitive Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0