

View Online at <https://aerobasegroup.com/nsn/5930-01-032-1895>

Thread Class:

2a

Body Style:

Bushing/hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Bushing Length:

0.609 inches

Body Length:

1.925 inches

Body Width:

0.688 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

1.985 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.188 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Pile-up Contact Form Arrangement:

1c single position

Thread Size:

0.469 inches

Switch Release Force:

3.0 ounces

Switch Actuating Force:

10.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.140 overtravel inches and 0.002 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 15.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0