NSN 5930-01-032-5423

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-032-5423

Body Style: Bushing mount Hazardous Locations/environmental Protection: Dustproof Bushing Length: 0.470 inches Body Length: 0.575 inches Body Width:
Hazardous Locations/environmental Protection: Dustproof Bushing Length: 0.470 inches Body Length: 0.575 inches
Dustproof Bushing Length: 0.470 inches Body Length: 0.575 inches
Bushing Length: 0.470 inches Body Length: 0.575 inches
0.470 inches Body Length: 0.575 inches
Body Length: 0.575 inches
0.575 inches
Body Width:
0.505 in all an
0.535 inches
Body Height:
0.640 inches
Case Material:
Plastic
Actuator Style:
Round
Actuator Diameter:
Between 0.420 inches and 0.430 inches
Actuator Height:
1.105 inches
Actuator Position-action Relationship:
Up position momentary and down position momentary and center position maintained
Actuator Position-locking Relationship:
Up position no locking action and down position locked out and center position no locking action
Actuator Color:
White single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
0.740 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Features Provided:
Actuator seal
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

NSN 5930-01-032-5423

Toggle Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac

inductive ac and 1.000 amperes lamp ac
Thread Series Designator:
Uns
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:

No

Fiig:

A053a0

Demilitarization: