

View Online at <https://aerobasegroup.com/nsn/5930-01-032-6812>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Body Diameter:**

0.640 inches

**Bushing Length:**

0.425 inches

**Body Length:**

1.040 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.500 inches

**Actuator Height:**

0.505 inches

**Actuator Color:**

Green single actuator

**Illuminated Actuator Color:**

Green single actuator

**Actuator Inscription:**

Panel hold single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thread Size:**

0.375 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.500 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 2.000 amperes lamp ac

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0