

View Online at <https://aerobasegroup.com/nsn/5930-01-033-0503>

Thread Class:

2b all threaded hole

Hazardous Locations/environmental Protection:

Moisture resistant and vibration resistant

Overall Length:

4.968 inches

Body Diameter:

Between 0.618 inches and 0.625 inches

Body Length:

3.593 inches

Overall Diameter:

1.750 inches

Longest Horizontal Distance Between Mounting Centers:

1.082 inches

Shortest Horizontal Distance Between Mounting Centers:

0.540 inches

Longest Vertical Distance Between Mounting Centers:

0.937 inches

Temperature Sensing Element Type:

Expanding shell

Operating Temperature Rating:

Between -100.0 degrees fahrenheit and 700.0 degrees fahrenheit

Mounting Method:

Flange and threaded hole

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.164 inches all threaded hole

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

-100.00/+600.00 actuation point degrees fahrenheit and -100.00/+600.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point screw and external deactuation point screw

Contact Voltage Rating In Volts:

240.0 ac at sea level second voltage

Special Features:

Packing gland on wire leads

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/flange

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0