NSN 5930-01-033-0518

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-033-0518
Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.875 inches
Body Length:
1.094 inches
Body Width:
0.400 inches
Body Height:
0.625 inches
Unthreaded Mounting Hole Diameter:
0.114 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.406 inches
Actuator Length:
0.810 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
0.810 inches
Actuator Roller Diameter:
0.190 inches
Actuator Roller Width:
0.190 inches
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

5.0 grams

Switch Actuating Force:

50.0 grams

Actuator Movement:

Between 0.047 pretravel inches and 0.045 overtravel inches and 0.013 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

 $250.000 \ \mbox{milliamperes}$ resistive dc and $10.000 \ \mbox{amperes}$ resistive ac

NSN 5930-01-033-0518

Sensitive Switch - Page 2 of 2



Terminal Type	And	Quantity:
---------------	-----	-----------

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0