## NSN 5930-01-033-2045

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-033-2045

Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
9.562 inches
Overall Height:
4.750 inches
Overall Width:
4.750 inches
First Flat Length:
1.125 inches single actuator
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
1.500 inches single actuator
Unthreaded Mounting Hole Diameter:
0.438 inches single mounting facility
Individual Section Quantity:
17
Knob Manufacturer Code:
82121
Longest Horizontal Distance Between Mounting Centers:
3.781 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
3.781 inches single mounting facility
End Application:
Ordalt 8253 89914
Switch Contact Basic Design:
Nonpile-up symmetrical
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
450.0 ac at sea level
Switch Actuator Momentary Position:
Clockwise single actuator
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:

Round, flatted, threaded hole single actuator

## **NSN 5930-01-033-2045**Rotary Switch - Page 2 of 2

A052b0



Terminal Type:
Tab w/screw
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
30.0 amperes resistive load dc at sea level
Special Features:
Sections one, three, five, seven, nine, eleven, thirteen, fifteen and seventeen are blank
Style Designator:
Tap, circuit selector
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: